



Inspiring green-energy since 2003



AE PLUS POLYCRYSTALLINE PV MODULES AE P6-72 Series 315W-345W

72 CELLS	MICRO-CRACK FREE	PID RESISTANT	SALT CORROSION RESISTANT	SAND RESISTANT	AMMONIA RESISTANT	HIGHLY STABLE AND TOUGH
--------------------	-------------------------	----------------------	---------------------------------	-----------------------	--------------------------	--------------------------------


✓ GERMAN QUALITY
AE Solar photovoltaic modules are produced using high quality materials, automated robotic lines, German technology and standards.

+ PLUS-SORTING
Higher yield due to plus-sorting from 0 up to +5 Wp guarantees the high system efficiency and yield stability.

🕒 PERFORMANCE GUARANTEE
AE Solar assures high investment, security and warranty claims by providing linear performance guarantee of 30 years and 12 years of product warranty.

📄 CERTIFICATES
Lining with international standards, AE Solar Photovoltaic modules are tested and certified under extreme stress conditions and it can bear harsh environment influences.

OUR PERFORMANCE GUARANTEE



30
years
Performance Guarantee

12
years
Product Warranty



Deutsche
Qualität
Garantiert

TECHNICAL DATA

AE P6-72 Series 315W-345W

SPECIFICATIONS

		AE315P6-72	AE320P6-72	AE325P6-72	AE330P6-72	AE335P6-72	AE340P6-72	AE345P6-72
Nominal Max. Power	P _{max} (Wp)	315	320	325	330	335	340	345
Maximum power voltage	V _{mp} (V)	36.66	36.75	36.83	36.97	37.05	37.09	37.18
Maximum power current	I _{mp} (A)	8.59	8.71	8.82	8.93	9.04	9.17	9.28
Open-circuit voltage	V _{oc} (V)	45.59	45.72	45.83	45.89	45.93	45.97	46.01
Short-circuit current	I _{sc} (A)	9.24	9.28	9.33	9.37	9.41	9.44	9.48
Module efficiency	(%)	16.23	16.49	16.75	17.01	17.26	17.52	17.78
Power tolerance	P _{max} (Wp)				0 / + 5			
Maximum system voltage DC	(V)	1000						
Operating temperature	(°C)	-40 to +85						
Temp. coefficients of P _{max}	(%/°C)	-0.40						
Temp. coefficients of V _{oc}	(%/°C)	-0.31						
Temp. coefficients of I _{sc}	(%/°C)	0.053						
Nom. Operating cell temp.(NOCT)	(°C)	45±2						

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m² with spectrum AM 1.5 and a cell temperature of 25°C.


MATERIAL CHARACTERISTICS

Cell type	Poly-crystalline 156.75mm x 156.75mm
No. of cells	72 (6 x 12)
Dimensions	1956 x 992 x 40mm
Weight	21 kg
Junction box	IP 67 MC 4 compatible
Output cable	1 x 4.0mm ² , 1200mm length or customised
Connector type	MC 4 compatible
Hail resistance	Max. Ø 28 mm, at 23 m/s
Wind load	2400 Pa / 244 kg/m ²
Mechanical load	5400 Pa / 550 kg/m ²

PACKAGING INFORMATION

Packing configuration	56pcs/double pallet	52pcs/double pallet
Loading Capacity	672 pcs / 40HQ	624 pcs / 40GP
Size / pallet (mm)	1990x1120x2410	1990x1120x2250
Weight	1300 kg / pallet	1192 kg / pallet

DIMENSIONS



CERTIFICATES



AES-DSH2019 V.002

All rights reserved. Specifications included in this data sheet are subject to change without notice.

AE Solar GmbH

Messerschmitzing 54
86343 Königsbrunn
Germany

Tel.: +49 8231 92 92 52 2
Fax: +49 8231 97 82 68 9
Email: sales@ae-solar.com
Web: www.ae-solar.com